

		QT-15			
HP	15		cfm@17	5 psi	51
Low Pressure_Bor	4.5"		Pump S <sub>I</sub>	peed	923
High Pressure_Bor	2.5"				
Stroke	3.5"				120 Gal H -
Max Working Pres	175		Dims (LxWxH)		78X28X55 -
Inlet Size	1" NPT		Weight		995 -
Air Outlet Size	1" BALL VALVE				
Min/Max RPM	600-1150 RPM				
Pump Life	50,000 HRS		Tank Pressure		200 psi
Duty Cycle	100%		Tank Fill Time		3.7 min
Lubrication	Quin-Cip				
Sump Capacity	3 qts. & 24 oz. (3.55 lit.)		Standard Warranty		Factory - 12 months parts / 12
Noise _dB(A)	84 ± 3		Extended Warr		3-Year Pump/ 2-Year Packa
Min operating_Temp	0 deg F		EWK part number		EWK-5
Max operating_Temp	104 deg F		EWK Contents		2 Air Filters, 12 qts Quin- Cip D
			*Duplex unit owners must purchase two (2) EWK kits *Engine-driven unit extended warranty is on air compressor only, "less engine". See engine manufacturer for warranty coverage.		
	Voltage: 120/1	230/1	200/3	230/3	460/3 575/3
	Amp Draw:	-	48.3	42	21 17

<sup>\*</sup>Applicable data doubled for Duplex models